

INSTALLATION FRAME FOR INTEGRATION OF MOTOR DRIVEN SCREENS ROLLO JUMBO IN SUSPENDED CEILINGS, BASED ON A FORM CLOSURE SOLUTION

- Frame profile to lay on plates of the suspended ceiling as an optical completion between screen housing and suspended ceiling plates.
- Enables convenient and visually attractive installation in suspended ceilings.
- Modular design allows the separate installation of screen and installation frame. In cases of maintenance, no ceiling specialist is needed.
- Hinged headpieces on both ends give the possibility of easy and comfortable removing of the screen housing in cases of maintenance.
- White colour of aluminium frame RAL-9003.
- Mounting set for installation is included in delivery.



Mounting set for installation is included in delivery



Visually attractive installation in suspended ceilings

Mod	Cross-section cm	Combination with projection screen width cm	Code no.	Weight brutto/netto kg	Package sizes cm
350	15	Rollo MAX 350 cm	91206	14 / 12	235x32x17
400	15	Rollo MAX 400 cm	91207	15 / 13	235x32x17
	20	Rollo MAX, Rollo MAX ALU - 400 cm	91217	15 / 13	235x32x17
	20	Rollo MAX Tension, Rollo MAX ALU Tension - 400 cm	91337	16 / 14	285x32x17
500	20	Rollo MAX, Rollo MAX ALU - 500 cm	91219	16 / 14	285x32x17
	20	Rollo MAX Tension, Rollo MAX ALU Tension - 500 cm	91339	17 / 15	285x32x17
600	20	Rollo MAX, Rollo MAX ALU - 600 cm	91221	17 / 15	335x32x17
	20	Rollo MAX Tension, Rollo MAX ALU Tension - 600 cm	91341	18 / 16	335x32x17